

SD-W

スチール製 スイッチ ドッグ(両錐型)



標準 **在庫品** **RHS**





SD-W-SR
(精度穴)



SD-W-ST
(メネジ)



SD-W-SR
(精度穴)



SD-W-ST
(メネジ)

本体
S45C
四三酸化鉄皮膜

品番	シャフト取付穴	D	d (H8)	M	L	L ₁	L ₂	θ	M ₁	黄銅ボール	質量 (g)	価格
SD25W30SR 8	精度穴	25	8	—	32	12	10	30°	M5×0.8 -5L	φ3.2	80	1,100
SD25W30SR10			10	—							75	1,100
SD25W30ST 8	メネジ	25	—	M 8×1.25	32	12	10	30°	M5×0.8 -5L	φ3.2	80	1,100
SD25W30ST10			—	M10×1.5							75	1,100
SD40W30SR12	精度穴	40	12	—	50	16	17	30°	M8×1.25-8L	φ6.4	310	1,700
SD40W30SR16			16	—							275	1,700
SD40W30ST12	メネジ	40	—	M12×1.75	50	16	17	30°	M8×1.25-8L	φ6.4	315	1,700
SD40W30ST16			—	M16×2							285	1,700
SD25W45SR 8	精度穴	25	8	—	24	12	6	45°	M5×0.8 -5L	φ3.2	80	800
SD25W45SR10			10	—							75	800
SD25W45ST 8	メネジ	25	—	M 8×1.25	24	12	6	45°	M5×0.8 -5L	φ3.2	80	800
SD25W45ST10			—	M10×1.5							75	800
SD40W45SR12	精度穴	40	12	—	36	16	10	45°	M8×1.25-8L	φ6.4	300	1,100
SD40W45SR16			16	—							275	1,100
SD40W45ST12	メネジ	40	—	M12×1.75	36	16	10	45°	M8×1.25-8L	φ6.4	300	1,100
SD40W45ST16			—	M16×2							275	1,100

使用例・使用方法

