


SRP-C,DRP-C レストパッド

標準 在庫品



材質の特性
P.2231

Fairlane





SRP-C
(スチール製)




DRP-C
(樹脂製)

M 六角穴付きボルト用



SRP-C
(スチール製)



DRP-C
(樹脂製)

| タイプ | 本体 |
|-------|---|
| SRP-C | スチール(SNCM220) 浸炭焼入 四三酸化鉄皮膜 HRC60 |
| DRP-C | ポリアセタール ホホワイト |

| スチール製 | | 樹脂製 | | D ($_{-0.13}^0$) | H | M | H ₁ |
|-----------|-------|-----------|-------|-----------------------|----|-----|----------------|
| 品番 | 質量(g) | 品番 | 質量(g) | | | | |
| SRP-100-C | 4 | DRP-100-C | 1 | 10 | 10 | M3 | 5 |
| SRP-120-C | 6 | DRP-120-C | | 12 | | M4 | |
| SRP-122-C | 7 | DRP-122-C | | 16 | M5 | 6.6 | |
| SRP-160-C | 11 | DRP-160-C | 2 | 20 | 10 | M6 | 7.6 |
| SRP-200-C | 18 | DRP-200-C | 3 | | | | |
| SRP-250-C | 32 | DRP-250-C | 6 | | | | |