


BJ153

内槽压板



本体
S45C
淬火回火
四氧化三铁膜

型号	L	W	H	W ₁	L ₂	M	L ₁	L ₃	夹紧力(kN) 突出量 max.~min.	容许紧固扭矩 (N·m)	质量 (g)			
BJ153-08040	40	19	12	9	6	M 8×1.25	10	32	5.3~7.3	17	50			
BJ153-08050	50				14			42	4~7.6		60			
BJ153-08063	63				27			55	3.1~8.3		70			
BJ153-10050	50	25	12	11	8	M10×1.5	12	40	8.5~11.9	34	80			
BJ153-10063	63				18			53	6.4~12.2		100			
BJ153-10080	80				32			70	7.4~17.7		170			
BJ153-10100	100	16	16	11	40	M10×1.5	15	90	8.8~18.8	45	220			
BJ153-10125	125				50			115	9.8~19.6		280			
BJ153-12063	63				14			14	52		13.7~21.6	71	190	
BJ153-12080	80	25	69	10.3~21	240									
BJ153-12100	100	40	89	10.9~25.8	350									
BJ153-12125	125	32	19	13	50	M12×1.75	20	114	12.9~27.5	80	440			
BJ153-12160	160							60	149		15.4~28.8	570		
BJ153-16080	80							19	17		18	65	16.6~26	115
BJ153-16100	100	38	25	17	30	M16×2	25	85	14.2~28.4	540				
BJ153-16125	125							45	110	14.7~31.1				
BJ153-16160	160							65	145	15.3~33.4	850			
BJ153-20160	160	50	25	21	60	M20×2.5	32	144	16.5~35.6	183	1140			
BJ153-20200	200							80	184		17.9~37.8	1440		

使用示例及使用方法

