

BJ610~611

接长螺栓

RHS SUS



IMAO



(钢铁制)



(不锈钢制)



类型		本体
BJ610 -06	BJ610 -08	S45C 淬火回火 四氧化三铁膜
BJ610 -10	BJ610 -12	S45C 四氧化三铁膜
BJ610 -16	BJ610 -20	
BJ611		
BJ610-SUS		SUS304

BJ610 BJ610-SUS

钢铁制		不锈钢制		M	H	L	Lf	W	质量 (g)
型	号	型	号						
BJ610-06020	BJ610-06020-SUS			M 6×1	20	10	12	10	13
BJ610-06025	BJ610-06025-SUS				25				17
BJ610-06032	BJ610-06032-SUS				32				20
BJ610-08025	—			M 8×1.25	25	13	16	13	25
BJ610-08032	—				32				35
BJ610-08040	—				40				45
—	BJ610-08025-SUS			M 8×1.25	25	13	16	14	32
—	BJ610-08032-SUS				32				40
—	BJ610-08040-SUS				40				50
BJ610-10032	BJ610-10032-SUS			M10×1.5	32	16	20	17	60
BJ610-10050	BJ610-10050-SUS				50				95
BJ610-10075	BJ610-10075-SUS				75				145
BJ610-12032	BJ610-12032-SUS			M12×1.75	32	18	20	22	95
BJ610-12050	BJ610-12050-SUS				50				165
BJ610-12075	BJ610-12075-SUS				75				250
BJ610-16032	—			M16×2	32	25	30	27	150
BJ610-16050	—				50				250
BJ610-16075	—				75				370
BJ610-20050	—			M20×2.5	50	30	30	30	290
BJ610-20075	—				75				430
BJ610-20100	—				100				580

BJ611

型 号	M	H	L	Lf	W	质量 (g)
BJ611-16032	M16×2	32	30	20	27	155
BJ611-16050		50		30		275
BJ611-16075		75		375		

特 点

请用于延长螺栓的长度。

使用示例及使用方法