

# HK-N-SUS

## 手柄旋钮 (不锈钢制)

HS SUS

IMAO



**HK-NR-SUS**

(高精度孔)






**HK-NT-SUS**

(内螺纹)

**HK-N-SUS**

(内螺纹贯通)

本体
不锈钢 (SCS13)
光磨



**HK-NR-SUS**

(高精度孔)

**HK-NT-SUS**

(内螺纹)

**HK-N-SUS**

(内螺纹贯通)

规格		D	D <sub>1</sub>	S	d (H7)	M	Lf	A	d <sub>1</sub>	Lf <sub>1</sub>
<b>HK-NR-SUS</b>	<b>32</b>	32	12	10	6	M 6×1	12	15	6.4	10
<b>HK-NT-SUS</b>	<b>40</b>	40	14	13	8	M 8×1.25	15	18	8.4	12
<b>HK-N-SUS</b>	<b>50</b>	50	18	17	10	M10×1.5	18	21	10.5	16
	<b>63</b>	63	20	21	12	M12×1.75	22	25	13	20

高精度孔			内螺纹			内螺纹贯通		
型 号	H	质量(g)	型 号	H	质量(g)	型 号	H	质量(g)
<b>HK32NR-SUS</b>	21	51	<b>HK32NT-SUS</b>	21	51	<b>HK32N-SUS</b>	20	49
<b>HK40NR-SUS</b>	26	96	<b>HK40NT-SUS</b>	26	96	<b>HK40N-SUS</b>	25	92
<b>HK50NR-SUS</b>	34	195	<b>HK50NT-SUS</b>	34	195	<b>HK50N-SUS</b>	32	190
<b>HK63NR-SUS</b>	42	360	<b>HK63NT-SUS</b>	42	350	<b>HK63N-SUS</b>	40	335

### 特点

高精度孔、内螺纹型，旋钮上面没有孔，最适用于食品机械和洗净机械。