

BJ153

溝付きストラップ

IMAO

標準 **在庫品** **RHS**



BJ153

(グリッパーなし)



BJ153-S

(セレーションタイプ)







BJ153-F

(フラットタイプ)



BJ153-E

(樹脂タイプ)



BJ153

(グリッパーなし)

BJ153-S

(セレーションタイプ)

BJ153-F **BJ153-E**

(フラットタイプ) (樹脂タイプ)

タイプ	本体	グリッパー
BJ153	S45C 焼入焼戻 四三酸化鉄皮膜	-
BJ153-S		SKH51 焼入焼戻
BJ153-F		HRC60~62
BJ153-E		ポリアセタール ホワイト

BJ153 (グリッパーなし)

品番	L	W	H	W ₁	L ₂	M	L ₁	L ₃	クランプ力(kN) 突出量 max.~min.	許容締付トルク (N・m)	質量 (g)	価格
BJ153-08040	40	19	12	9	6	M 8×1.25	10	32	5.3~ 7.3	17	50	1,620
BJ153-08050	50				14			4 ~ 7.6	60		1,740	
BJ153-08063	63				27			3.1~ 8.3	70		1,850	
BJ153-10050	50	25	12	11	8	M10×1.5	12	40	8.5~11.9	34	80	1,850
BJ153-10063	63				18			6.4~12.2	100		1,970	
BJ153-10080	80				32			7.4~17.7	170		2,100	
BJ153-10100	100				40			8.8~18.8	220		2,400	
BJ153-10125	125	32	16	13	50	M12×1.75	15	115	9.8~19.6	45	280	2,700
BJ153-12063	63				14			13.7~21.6	190		2,300	
BJ153-12080	80				25			10.3~21	240		2,600	
BJ153-12100	100	32	19	13	40	M12×1.75	20	89	10.9~25.8	80	350	3,100
BJ153-12125	125				50			12.9~27.5	440		3,400	
BJ153-12160	160				60			15.4~28.8	570		3,800	
BJ153-16080	80				17			16.6~26	320		3,100	
BJ153-16100	100	38	25	17	30	M16×2	18	85	14.2~28.4	115	540	3,500
BJ153-16125	125				45			14.7~31.1	670		4,100	
BJ153-16160	160				65			15.3~33.4	850		4,500	
BJ153-20160	160	50	25	21	60	M20×2.5	32	144	16.5~35.6	183	1140	4,900
BJ153-20200	200				80			17.9~37.8	1440		5,500	

BJ153-S (セレーションタイプ)

品番	L	W	H	W ₁	L ₂	M	D	H ₁	L ₁	L ₃	L ₄	クランプ力(kN) 突出量max.~min.	許容締付トルク (N・m)	質量 (g)	価格
BJ153-08063-S	63	19	12	9	20	M 8×1.25	6	1.5	19	55	7	3.1~ 6.9	17	75	5,400
BJ153-08080-S	80				72					4.1~ 7.8		100		5,700	
BJ153-10080-S	80	25	16	11	24	M10×1.5	8.5	2.5	23	70	9	5.6~11.4	34	180	6,300
BJ153-10100-S	100				90					6.6~12.7		230		6,500	
BJ153-12080-S	80	32	19	13	18	M12×1.75	10	3.5	27	69	10	8.4~14.7	58	290	7,500
BJ153-12100-S	100				89					7.9~16.9		360		7,900	
BJ153-12125-S	125				43					114		9.3~18.5		450	8,200
BJ153-16100-S	100	38	25	17	23	M16×2	12	4	32	85	12	12.7~22.4	115	560	9,300
BJ153-16125-S	125				110					13.1~25.5		690		9,700	
BJ153-16160-S	160				58					145		13.6~28		870	10,300

BJ153-F (フラットタイプ)

品番	L	W	H	W ₁	L ₂	M	D	H ₁	L ₁	L ₃	L ₄	クランプ力(kN) 突出量max.~min.	許容締付トルク (N・m)	質量 (g)	価格
BJ153-08063-F	63	19	12	9	20	M 8×1.25	6	1.5	19	55	7	3.1~ 6.9	17	75	5,100
BJ153-08080-F	80				72					4.1~ 7.8		100		5,300	
BJ153-10080-F	80	25	16	11	24	M10×1.5	8.5	2.5	23	70	9	5.6~11.4	34	180	5,900
BJ153-10100-F	100				90					6.6~12.7		230		6,100	
BJ153-12080-F	80	32	19	13	18	M12×1.75	10	3.5	27	69	10	8.4~14.7	58	290	7,100
BJ153-12100-F	100				89					7.9~16.9		360		7,500	
BJ153-12125-F	125				43					114		9.3~18.5		450	7,900
BJ153-16100-F	100	38	25	17	23	M16×2	12	4	32	85	12	12.7~22.4	115	560	9,000
BJ153-16125-F	125				110					13.1~25.5		690		9,400	
BJ153-16160-F	160				58					145		13.6~28		870	9,900

BJ153-E (樹脂タイプ)

品番	L	W	H	W ₁	L ₂	M	D	H ₁	L ₁	L ₃	L ₄	クランプ力(kN) 突出量max.~min.	許容締付トルク (N・m)	質量 (g)	価格
BJ153-08063-E	63	19	12	9	20	M 8×1.25	6	1.5	19	55	7	1 ~2.3	5	75	4,800
BJ153-08080-E	80				72					1.3~2.5		100		5,100	
BJ153-10080-E	80	25	16	11	24	M10×1.5	8.5	2.5	23	70	9	1.9~3.9	10	180	5,700
BJ153-10100-E	100				90					2.2~4.1		230		5,900	
BJ153-12080-E	80	32	19	13	18	M12×1.75	10	3.5	27	69	10	2.9~5	17	290	6,900
BJ153-12100-E	100				89					2.6~5.6		360		7,200	
BJ153-12125-E	125				43					114		3 ~5.9		450	7,600
BJ153-16100-E	100	38	25	17	23	M16×2	12	4	32	85	12	4.4~7.7	34	560	8,700
BJ153-16125-E	125				110					4.3~8.5		690		9,200	
BJ153-16160-E	160				58					145		4.4~9		870	9,600

使用例・使用方法
