

BTK

タップド ブラインド ノブ

標準 在庫品

RHS

SUS

材質の特性
P.2231

追加加工

ネジ
カット

ネジ
組付け

P.2200~

Original ELESA Model VC.192



elesta




(メネジ)



(オネジ)



(メネジ)



(オネジ)

★One Point
フラット形状で汚れにくい

タイプ	ノブ	メネジ	オネジ
BTK	フェノール樹脂 光沢仕上げ	黄銅 (カドミウム低減材)	S10C 亜鉛メッキ
BTK-SUS	ブラック	SUS303	SUS303

■メネジ

黄銅製		SUS製		D	M	H	D ₁	S	Lf
品番	質量(g)	品番	質量(g)						
BTK25	11	—	—	25	M 4×0.7	21	15	9	10
BTK30A	16	—	—	32	M 5×0.8	23	19	11	
BTK30B	19	BTK30-SUS	18		M 6×1				27
BTK40A	27	—	—	40	M 8×1.25	33	25	14	
BTK40B	31	BTK40-SUS	30						50
BTK50A	50	—	—	60	M12×1.75	44	30	20	
BTK50B	52	BTK50-SUS	50						70
BTK60A	76	—	—	85					
BTK60B	80	BTK60-SUS	78						
BTK70	119	—	—						
BTK85	176	—	—						

■オネジ

スチール製			SUS製		D	M	H	D ₁	S	L			
品番	質量(g)	品番	質量(g)										
BTK25 ×10	11	—	—	25	M 5×0.8	21	15	9	10				
BTK25 ×16	12	—	—						16				
BTK25A×10	10	—	—						10				
BTK25A×16	12	—	—						16				
BTK25A×20	14	—	—						20				
BTK25A×30	18	—	—		30								
BTK30 ×10	17	BTK30×10-SUS	17		32				M 6×1	23	19	11	10
BTK30 ×16	18	BTK30×16-SUS	18										16
BTK30 ×20	20	BTK30×20-SUS	20										20
BTK30 ×35	25	BTK30×35-SUS	25										35
BTK30A×20	24	—	—	20									
BTK30A×30	27	—	—	30									
BTK30A×40	29	—	—	40									
BTK40A×20	30	—	—	40		M 6×1	27	21	12				20
BTK40A×30	32	—	—										30
BTK40 ×16	35	—	—										16
—	—	BTK40×20-SUS	36		20								
BTK40 ×25	38	BTK40×25-SUS	38		25								
—	—	BTK40×30-SUS	39		30								
BTK40 ×35	40	BTK40×35-SUS	40		35								
BTK40 ×45	43	BTK40×45-SUS	43		45								
BTK50A×16	52	—	—		50	M 8×1.25				33	25	14	16
BTK50A×20	53	—	—										20
BTK50A×25	55	—	—	25									
BTK50A×30	56	—	—	30									
BTK50A×40	60	—	—	40									
BTK50 ×20	63	BTK50×20-SUS	63	20									
BTK50 ×30	66	BTK50×30-SUS	66	30									
BTK50 ×40	70	BTK50×40-SUS	70	40									
BTK50 ×50	73	BTK50×50-SUS	73	50									
BTK60 ×20	87	—	—	60			M10×1.5	37	27				17
BTK60 ×30	92	—	—		30								
BTK60 ×40	98	—	—		40								
BTK60 ×50	101	—	—		50								
BTK60 ×25B	105	—	—		25								
BTK60 ×30B	110	BTK60×30-SUS	110		30								
BTK60 ×40B	118	BTK60×40-SUS	118		40								
BTK60 ×50B	128	BTK60×50-SUS	128		50								

特長

- ・SUS製はネジ部にSUSを用いた製品で、食品機械、衛生機器に最適です。
- ・フラット形状で汚れにくいです。

技術データ

使用温度 max.110℃ min.-20℃

追加加工を承ります!

