

# KN,KS

# ナールド ノブ

標準  
在庫品

RHS

SUS

材質の特性  
P.2231

追加加工

ネジ  
カット  
ネジ  
締付け  
P.2200~

Original ELESA Model B.193

elasa



(スチール製)



(SUS製)




KS  
(オネジ)




KN  
(メネジ)




KN-T  
(メネジ貫通)



KN KN-SUS  
(メネジ)



KN-T  
(メネジ貫通)



KS KS-SUS  
(オネジ)

タイプ	ノブ	メネジ	オネジ
KN	フェノール樹脂 光沢仕上げ ブラック	黄銅 (カドミウム低減材)	—
KN-T		SUS303	—
KN-SUS			—
KS		—	S10C 亜鉛メッキ
KS-SUS		—	SUS303

KN KN-SUS (メネジ)

黄銅製		SUS製		D	M	H	D <sub>1</sub>	S	質量 (g)
品番	Lf	品番	Lf						
KN15C	6	—	—	15	M 3×0.5	11	11	2	4
KN15		—	—		M 4×0.7				
KN15B	5	KN15B-SUS	6	18	M 5×0.8	12	13	3	5
KN18		—	—		M 6×1				
KN20	6	KN20 -SUS	6	22	M 6×1	14	15	4	8
KN25	10	KN25 -SUS	10	26					
KN30		KN30 -SUS		31	24	20			
KN35		—		—	—	36	23	27	8
KN40	13	—	—	40	M10×1.5	26	29	10	38
KN50A	17	—	—	50					M12×1.75
KN50B	20	—	—		—	—	—	—	

**KN-T (メネジ貫通)**

品番	D	M	H	D <sub>1</sub>	S	L <sub>f</sub>	d <sub>2</sub>	質量 (g)
KN15T	15	M 4×0.7	11	11	2	10	6	4
KN18T	18	M 5×0.8	12	13	3		7	5
KN20T	22	M 6×1	14	15	4	11	8	8
KN25T	26		M 8×1.25	18	19	6	15	10
KN25T A		17						
KN30T	31	M 8×1.25	18	24	6	15	13	21
KN30T A								24
KN40T	40	M10×1.5	26	29	10	15	14	40

**KS | KS-SUS (オネジ)**

スチール製 品番	SUS製 品番	D	M	H	D <sub>1</sub>	S	L	質量 (g)
KS15×6C	KS15×6C-SUS	15	M 3×0.5	11	11	2	6	3
KS15×10C	KS15×10C-SUS						10	4
KS15×6A	KS15×6A-SUS		6				3	
KS15×10A	KS15×10A-SUS		10				4	
KS15×16A	KS15×16A-SUS		16				5	
KS15×10B	KS15×10B-SUS		10					
KS15×16B	KS15×16B-SUS		16				6	
KS18×10	—	18	M 5×0.8	12	13	3	10	7
KS18×16	—						16	
KS20×10	KS20×10 -SUS	22	M 6×1	14	15	4	10	9
KS20×16	KS20×16 -SUS						16	10
KS20×25	—						25	12
KS25×16	KS25×16 -SUS	26	M 6×1	18	19	6	16	14
KS25×25	KS25×25 -SUS						25	16
KS25×16A	—						16	20
KS25×25A	—						25	23
KS30×16	—	31	M 8×1.25	18	24	6	16	25
KS30×25	—						25	28
KS30×40	—						40	32
KS35×25	—	36	M 8×1.25	23	27	8	25	38
KS35×40	—						40	42
KS40×30	—	40	M10×1.5	26	29	10	30	59
KS50×40	—	50		32	36	12	40	94

**技術データ**

使用温度 max.110℃ min.-20℃

**追加工を承ります!**
