


VD4

防振ゴム(片側オネジ)

標準 在庫品 R4HS

Original ELESA Model DVA 

本体	オネジ
天然ゴム(NR) ショアA55±5 ブラック	SS400 亜鉛メッキ

品番	D	H	M	L	最大荷重 (N)	最大たわみ (mm)	バネ定数 (N/mm)	質量 (g)
VD4-0808M 3	8	8	M 3×0.5	6	55	2	28	3
VD4-1010M 4	10	10	M 4×0.7	10	88	2.5	35	2
VD4-1015M 4		15			92	3.75	25	3
VD4-1510M 4	15	10	M 4×0.7	10	168	2	84	4
VD4-1515M 4		15			259	3.75	69	5
VD4-1520M 4		20			223	5	45	7
VD4-1530M 4		30			258	7.5	34	9
VD4-2010M 6	20	10	M 6×1	18	645	2.5	258	15
VD4-2015M 6		15			468	3.75	125	10
VD4-2020M 6		20			367	5	73	13
VD4-2030M 6		30			420	7.5	56	23
VD4-2515M 6	25	15	M 6×1	18	797	3.75	213	18
VD4-2517M 6		17			833	4.25	196	20
VD4-2520M 6		20			581	5	116	20
VD4-2530M 6		30			591	7.5	79	25
VD4-3015M 8	30	15	M 8×1.25	20	1023	3.75	273	30
VD4-3017M 8		17			1275	4.25	300	31
VD4-3020M 8		20			1014	5	203	35
VD4-3025M 8		25			1026	6.25	164	38
VD4-3030M 8	40	30	M 8×1.25	23	776	7.5	103	43
VD4-4020M 8		20			2500	5	500	55
VD4-4025M 8		25			1660	6.25	266	60
VD4-4030M 8		30			1480	7.5	197	73
VD4-4040M 8	50	40	M 10×1.5	28	1403	10	140	83
VD4-5020M10		20			3460	5	692	90
VD4-5030M10		30			2520	7.5	336	118
VD4-5040M10		40			2760	10	276	140

参照ページ

選定に関する製品情報および注意事項は、「防振ゴム
使用の手引き」をご覧ください。(P. 1194 参照)