


# VDF6

# 防振ゴム(円錐台、オネジ)

標準 **在庫品** **RHS** **SUS**

Original ELESA Model DVF **eleasa**



本体	オネジ
シリコンゴム(MVQ) ショアA55±5 グレー	SUS304

## ★One Point

SUS+シリコンゴム製で食品・医療関連に最適

品番	D	H	M	D <sub>1</sub>	L	最大荷重 (N)	最大たわみ (mm)	バネ定数 (N/mm)	質量 (g)							
VDF6-2017M 5L06M-SUS	20	17	M 5×0.8	10	6	197	4.25	46	14							
VDF6-2017M 5L10M-SUS					10				15							
VDF6-2017M 5L20M-SUS					20				17							
VDF6-2017M 6L12M-SUS					12				16							
VDF6-2017M 6L18M-SUS					18				17							
VDF6-2017M 6L25M-SUS					25				19							
VDF6-2517M 6L08M-SUS	25	17	M 6×1	19	8	580	4.25	137	18							
VDF6-2517M 6L12M-SUS					12				19							
VDF6-2517M 6L18M-SUS					18				20							
VDF6-2517M 6L25M-SUS					25				21							
VDF6-3222M 8L10M-SUS	32	22	M 8×1.25	24	10	751	5.5	150	30							
VDF6-3222M 8L16M-SUS					16				32							
VDF6-3222M 8L23M-SUS					23				35							
VDF6-3222M 8L30M-SUS					30				37							
VDF6-3835M 8L10M-SUS					38				35	M 8×1.25	30	10	1311	8.75	150	70
VDF6-3835M 8L16M-SUS												16				74
VDF6-3835M 8L30M-SUS	30	79														
VDF6-3835M10L12M-SUS	12	75														
VDF6-3835M10L20M-SUS	20	79														
VDF6-3835M10L28M-SUS	28	82														
VDF6-4350M10L40M-SUS	40	86														
VDF6-4350M10L12M-SUS	43	50	M10×1.5	40	12	1318	12.5	105	98							
VDF6-4350M10L20M-SUS					20				101							
VDF6-4350M10L28M-SUS					28				105							
VDF6-4350M10L40M-SUS					40				110							
VDF6-5020M10L12M-SUS	50	20	M10×1.5	40	12	2890	5	578	72							
VDF6-5020M10L20M-SUS					20				75							
VDF6-5020M10L28M-SUS					28				78							
VDF6-5020M10L40M-SUS					40				82							

### 技術データ

使用温度 max.200℃ min.-50℃

### 参照ページ

選定に関する製品情報および注意事項は、「防振ゴム使用の手引き」をご覧ください。(P. 1194 参照)